

EIKON

RM8

RIBBON STUDIO MICROPHONE
USER'S MANUAL



ENGLISH

EIKON

General

Thank you for buying the EIKON RM8 Professional Ribbon microphone.

The RM8 ribbon microphone is made following the strictest construction standards which make it the ideal microphone for any professional application.

Equipped with Double-sided 0,02 mm pure aluminum foil for an excellent vocal range and acoustic instruments image, even in the most difficult mixing circumstances.

The package includes a shockmount support, anti-pop filter and a sturdy aluminum carrying case.

Features

- Double - sided 0,02 mm pure aluminium foil
- Equal sensitivity from front or back of element
- Absence of high frequency phase distortion
- Very high overload characteristics
- Low frequency attenuation switch
- Wide low - frequency range and fast transient response


Specifications

- Polar Pattern:** Bi- directional (Figure – 8)
- Frequency response:** 20Hz- 20Khz
- Sensitivity:** -34dB \pm 2 dB (0dB = 1 V Pa, 1 KHz)
- Nominal Impedance:** 200 Ω
- Load Impedance:** \geq 1K Ω
- Self Noise:** 15 db-A
- S/N Ratio:** 79 db
- Max input Spl:** 130 db
- Filter:** High-pass 100Hz 12db/oct
- Pad:** 0 / -10 db
- Phantom Power Requirement:** 48 v Dc Phantom
- Connector:** xlr 3 Pin
- Weight:** 475 g
- Dimensions:** L 190 mm x 50 mm 0
- Accessories:** Shock mount, popscreen

Product complies with CE regulations **CE**

Polar pattern and Frequency Chart

Figure of 8



EIKON

Is a brand of

PROEL S.p.A.

(World Headquarters - Factory)

Via alla Ruenia 37/43

64027 Sant'Omero (Te) – Italy

Tel: +39 0861 81241

Fax: +39 0861 887862

www.eikon-audio.com

EIKON