



CONCORDE MKII  
UNIVERSAL  
**USERGUIDE**

ortofon

# CONCORDE MKII UNIVERSAL **USERGUIDE**

Thank you for choosing the Ortofon Moving Magnet cartridge. At Ortofon we constantly look for new technology to be used in our products, thus we assure the highest level of performance and quality. It is our aim to bring you many hours of new and surprising experience in listening to your precious collection.

## **WARNING**

This phono cartridge is only for mounting on tonearms and must not be used for other purposes.

## **PLEASE NOTE**

To avoid damages on the stylus please keep the stylus guard on the cartridge any time when mounting or dismantling the unit.

## **MOUNTING THE CONCORDE CARTRIDGE**

Ortofon Concorde cartridge is for direct and easy mounting on the tonearm, no alignment is required.

## **THE OPTIMUM TRACKING WEIGHT SETTING:**

Tracking Force Recommended refers to the optimal weight which will result in the best combination of groove holding and sound. Take care not to deviate outside of the Tracking Force Range, as it may result in skipping, poor sound quality, or unnecessary wear on your vinyl.

## **STYLUS CARE**

- Remove dust carefully from record surfaces by using a fine antistatic brush before every use.
- We do not recommend the use of solvents of any kind for cleaning of either record surface or stylus, as they can weaken the stylus or cause damage to the internal components of the cartridge.
- For cleaning the stylus, use stylus brush a few times along the cantilever in the direction of the stylus tip, whenever you play a new record or change sides. Use the brush in the forward direction from the rear of the cartridge towards the stylus tip and never from stylus tip to the rear of the cartridge and never from side to side.
- Remove dust from the diamond tip before and after playback of each record.
- Make sure to follow setup guidelines as suggested by the specifications found in the manual (or found on our website).



## CONCORDE

Output voltage at 1,000 Hz, 5 cm/sec.

Channel balance at 1 kHz

Channel separation 1 kHz

Channel separation 15 kHz

Frequency range at -3 dB

Tracking ability at 315 Hz  
at recommended tracking force

Compliance, dynamic lateral

Stylus type

Tracking force range

Tracking force recommended

Cartridge weight

Replacement stylus unit

## MIX

6 mV

1.5 dB

20 dB

15 dB

20 – 20,000 Hz

100 µm

14 µm/mN

Spherical  
R 18 µm

2 – 4 g

3 g

18.5 g

Mix



## DJ

6 mV

1 dB

22 dB

15 dB

20 – 20,000 Hz

100 µm

14 µm/mN

Spherical  
R 18 µm

3 – 5 g

4 g

18.5 g

DJ



## CLUB

8 mV

1 dB

25 dB

15 dB

20 – 20,000 Hz

100 µm

14 µm/mN

Special Elliptical  
r/R 13/25 µm

2 – 4 g

3 g

18.5 g

Club



## SCRATCH

10 mV

1 dB

22 dB

15 dB

20 – 18,000 Hz

120 µm

14 µm/mN

Spherical  
R 18 µm

3 – 5 g

4 g

18.5 g

Scratch



## DIGITAL

10 mV

1 dB

22 dB

15 dB

20 – 18,000 Hz

100 µm

14 µm/mN

Spherical  
R 18 µm

3 – 5 g

4 g

18.5 g

Digital





Get more information about  
Ortofon DJ cartridges

For more information please refer to Ortofon DJ FAQ:  
[www.ortofon.com/support/support-dj/faq-setup](http://www.ortofon.com/support/support-dj/faq-setup)

Ortofon A/S  
Stavangervej 9  
DK-4900 Nakskov  
Denmark  
support@ortofon.dk  
www.ortofon.com

10-17/5-800150-12