

Portable Speakers

MILAN M10

600 Watt 2 Way 10"
Full Range Powered Loudspeaker with
KLARK TEKNIK DSP Technology for
Portable PA and Installation Applications

- 2 way full range powered loudspeaker for portable PA and installation applications
- 600 Watt power featuring KLARK TEKNIK Class-D technology
- KLARK TEKNIK Digital Signal Processing for total system control
- High excursion 10" low frequency driver with low mass voice coil for improved transient response
- 1" high temperature dome compression driver with extended high frequency reproduction
- Converging elliptical waveguide provides wide dispersion and excellent pattern control
- Speech/music switch featuring optimised equalisation for voice or music applications
- Switchable 100 Hz high pass filter for subwoofer integration
- Lightweight composite enclosure with black finish
- Rugged powder coated perforated steel mesh grille
- Dual angle pole mount for accurate audience coverage
- Multiple internal rigging points for installation applications
- 3-Year Warranty Program*
- Designed and engineered in England



The MILAN M10 is a portable 10" two-way powered loudspeaker featuring two independent input channels, mic and line inputs, two band EQ, intelligent limiting, and a Mix Out function for connection to additional MILAN loudspeakers for easy system expansion.



The Class-D amplifier is a two channel unit with an integrated electronic crossover, allowing the HF and LF drivers to be powered separately without one being able to influence the sound of the other. Total output power is 600 watts peak, providing plenty of headroom to maintain good dynamic range so that transient signals are delivered effortlessly. The lightweight switch-mode power supply couples with industry leading KLARK TEKNIK digital signal processing, providing dynamic equalisation and sophisticated limiting functions to ensure optimum performance and long term reliability.

Portable Speakers

MILAN M10

600 Watt 2 Way 10"
Full Range Powered Loudspeaker with
KLARK TEKNIK DSP Technology for
Portable PA and Installation Applications

The two discrete input channels are each equipped with balanced combination jack/XLR connectors and a level control, catering for a broad range of music sources from low impedance microphones, acoustic guitars and keyboards, to mp3 players and mixing consoles, selectable via a mic/line slide switch.

Common to both channels are bass and treble controls with ± 6 dB of cut or boost to allow the loudspeaker to be equalised to the venue. In addition, a low cut filter is provided at 100 Hz to shelve the low frequency response when used on the floor as a wedge monitor, or to ensure correct integration with subwoofers. A speech/music switch optimises the loudspeaker's frequency response either for predominantly vocal material or for music programme. A Mix Out function sends the mix of both input channels post-EQ to additional MILAN loudspeakers on a balanced male XLR for easy system expansion.

The trapezoidal enclosure is fabricated from high density polypropylene, and is extensively ribbed externally and internally to eliminate resonances and also to provide an attractive and durable cabinet finish. The symmetrical side angles allow the loudspeaker to be conveniently used as a floor monitor. The recessed grab handle on the top is designed for easy lifting and carrying, while the dual angle pole mount socket allows the loudspeaker to be mounted on straight poles or speaker stands either vertically, or raise higher and angled down to optimise audience coverage. A total of six M10 rigging points are provided on the top and bottom of the cabinet to enable vertical or horizontal suspension in permanent installations using M10 shoulder eyebolts.

Mains power is connected via a non-locking IEC receptacle with integrated fuseholder. The illuminated front badge can operate in one of three possible modes: permanently on; permanently off; or to indicate the action of limiting.

Rigging

The MILAN M10 loudspeaker can be wall mounted using the PB-55 universal wall bracket with the built in pole mount socket.

It can also be suspended in permanent installations using shoulder eyebolts attached to the M10 rigging points provided on the top and bottom of the cabinet. The loudspeaker can be oriented either vertically or horizontally to suit the available venue space.

Portable Speakers

MILAN

M10

600 Watt 2 Way 10"
Full Range Powered Loudspeaker with
KLARK TEKNIK DSP Technology for
Portable PA and Installation Applications

A&E Specifications

The system shall be of the two-way self-powered type consisting of one 10" (254 mm) low frequency loudspeaker and one 1" (25 mm) aluminium diaphragm high frequency compression driver together with an integrated Class-D amplifier providing two independent input channels with microphone and line inputs, bass and treble equalisation, low cut filter, speech/music contour and Mix Out function. Performance specifications of a typical production unit shall meet or exceed the following: frequency response, measured with swept sine wave input, shall be flat within ± 3 dB from 55 Hz to 18 kHz, and within -10 dB from 50 Hz to 20 kHz. Nominal dispersion, at -6 dB points, shall average 90° H x 60° V. Maximum SPL measured with music program input shall be 126 dB (peak).

Dimensions: 522 mm high x 329 mm wide x 294 mm deep (20.6" x 13" x 11.6"). Net weight: 13.3 kg (29.3 lbs). The loudspeaker system shall be the Turbosound MILAN M10. No other loudspeaker shall be acceptable unless submitted data from an independent test laboratory verify that the above combined performance / size specifications are equalled or exceeded.

Portable Speakers

MILAN

M10

600 Watt 2 Way 10"

Full Range Powered Loudspeaker with
KLARK TEKNIK DSP Technology for
Portable PA and Installation Applications

Technical Specifications

Dimensions (H x W x D)

522 x 329 x 294 mm (20.6 x 13 x 11.6")

Net Weight

13.3 kg (29.3 lbs)

Components

1 x 10" (254 mm) LF driver, 1 x 1" (25 mm) HF compression driver

Frequency Response

55 Hz – 18 kHz ± 3 dB, 50 Hz – 20 kHz -10 dB

Nominal Dispersion

90° H x 60° V @ -6 dB points

Maximum SPL

126 dB (peak)

Construction

Injection-moulded polypropylene enclosure.
Recessed carrying handle. Integral dual-angle pole mount socket

Grille

Powder coated galvanised perforated steel mesh grille with foam backing

Connectors

Mic/Line input: combo jack/female XLR wired pin 2 hot;
Mix out: male XLR wired pin 2 hot; IEC mains connector with integrated fuseholder

Controls

Level, Line/Mic, Low Cut, Speech/Music, Bass and Treble, Front LED, Mains on/off

Indicators

Power LED (blue), SIG LED (green), LIMIT LED (red), CLIP LED (red)

Amplifier

Type:	Class-D
Max Output Power:	LF: 500 W; HF: 100 W
Input Sensitivity:	Mic: -32 dBu; Line: -2 dBu
Input Impedance:	Mic: 560 Ω unbalanced, 1 k Ω balanced Line: 20 k Ω unbalanced, 40 k Ω balanced
Equalisation:	Bass: ± 6 dB @ 80 Hz; Treble: ± 6 dB @ 12 kHz
Amplifier Protection:	Full short circuit, open circuit, thermal

Mains Voltage

USA / CAN:	100–120V~ (T 6.3 A H 250 V)
UK / AUS / EUR:	220–240V~ (T 3.15 A H 250 V)
CH:	220–240V~ (T 3.15 A H 250 V)
JP:	100–120V~ (T 6.3 A H 250 V)

Power Consumption

80 W @1/8 max power

Rigging Options

(6) M10 threaded internal rigging points

Spares And Accessories

LS-1032	10" (254 mm) replacement LF loudspeaker
RC-1032	Recone kit
CD-125	1" (25 mm) HF compression driver
RD-125	HF diaphragm
AMP-M10	Replacement amplifier assembly
PB-55	Wall bracket, pole mount fixing
EB-10	M10 shoulder eyebolt

Portable Speakers

MILAN M10

600 Watt 2 Way 10"
Full Range Powered Loudspeaker with
KLARK TEKNIK DSP Technology for
Portable PA and Installation Applications



Portable Speakers

MILAN M10

600 Watt 2 Way 10"
Full Range Powered Loudspeaker with
KLARK TEKNIK DSP Technology for
Portable PA and Installation Applications



Portable Speakers

MILAN M10

600 Watt 2 Way 10"
Full Range Powered Loudspeaker with
KLARK TEKNIK DSP Technology for
Portable PA and Installation Applications



Portable Speakers

MILAN M10

600 Watt 2 Way 10"
Full Range Powered Loudspeaker with
KLARK TEKNIK DSP Technology for
Portable PA and Installation Applications



For service, support or more information contact the TURBOSOUND location nearest you:

Europe
MUSIC Group Services UK
Tel: +44 156 273 2290
Email: CARE@music-group.com

USA/Canada
MUSIC Group Services NV Inc.
Tel: +1 702 800 8290
Email: CARE@music-group.com

Japan
MUSIC Group Services JP K.K.
Tel: +81 3 6231 0454
Email: CARE@music-group.com

MUSIC Group accepts no liability for any loss which may be suffered by any person who relies either wholly or in part upon any description, photograph, or statement contained herein. Technical specifications, appearances and other information are subject to change without notice. All trademarks are the property of their respective owners. MIDAS, KLARK TEKNIK, TURBOSOUND, BEHRINGER and BUGERA are trademarks or registered trademarks of MUSIC Group IP Ltd. © MUSIC Group IP Ltd. 2014 All rights reserved.

